

F/CE

SPECIALTY

30 - 50 - 70



MCCORMICK

Tractor Model		X4.30F/GE ROPS	X4.50F/GE ROPS	X4.70F/GE ROPS
Engine				
Rated Engine HP @ 2200 RPM (ISO)	HP (kW)	71 (52)	90 (66)	102 (75)
Max Engine HP @ 2200 RPM (ISO)	HP (kW)	75 (55)	95 (70)	111 (81.6)
Max. Engine Torque @ 1600 RPM	lb ft (Nm)	200 (272)	278 (378)	302 (410)
Engine Type	DEUTZ liquid cooled diesel engine; EPA Tier 4 final compliant using <i>only</i> cooled EGR + DOC system (<i>no regeneration</i>)			
Engine Size	2.9 Liter, 4-cylinder			
Fuel / DEF Capacity	gal (liter)	17 (65)		
Drive Train				
Standard Transmission	16 x 16 speeds with creeper gear; synchronized mechanical shuttle: 25 mph (40 kph) transport speed			
Optional Transmission (1)	15 x 15 speeds; hydraulic power shuttle: 25 mph (40 kph) transport speed			
Optional Transmission (2)	40 x 40 speeds with creeper gear & 2-speed power shift; hydraulic power shuttle; 25 mph (40 kph) transport speed			
Clutch	Independent dual dry clutch standard; 11 inch			
Brakes	Heavy duty wet multi-disc disc brakes			
Differential Lock	Limited slip			
4wd Front Axle	Electro-hydraulic engagement with integrated front axle brakes			
Hydraulics, 3-point Hitch, PTO				
Standard Hydraulic Pump	gpm (lpm)	Double Pump: 20.6 (78) total flow: Dedicated steering pump 7.4 (28); implement pump 13.2 (50)		
Standard Rear Remote Valves	2 valves; 1 standard + 1 float			
Optional Rear Remote Valves (1)	2 valves; 1 motor with flow divider + 1 float			
Optional Rear Remote Valves (2)	2 valves; 1 motor with flow divider + 1 kick out			
Standard Rear 3-point Hitch Type	Category 2 with fixed ball ends; mechanical lift control			
Optional Rear 3-point Hitch Type	Category 2 with quick attach hooks; electronic lift control option (<i>F Series Only</i>)			
Rear 3-point Lift Capacity	lb (kg)	5,732 (2600) standard		
Rear PTO	2 Speeds (540/1000 rpm) standard; groundspeed PTO optional			
Operator's Area				
ROPS Area	Open Station ROPS; rubber footdeck with adjustable steering wheel and suspended seat			
Seat and Front Dash	Deluxe air suspended seat; tilt and telescopic steering wheel			
Wheelbase	in (mm)	84 (2134)		
Height Over ROPS	in (mm)	89 (2261)		
Overall Length	in (mm)	112 (2845)		
Minimum Width	in (mm)	F: 44 (1118) GE: 47.5 (1208)		
Base Weight <small>without ballast</small>	lb (kg)	5,842 (2650)		

All above specifications are manufacturer's calculated estimates.