

X1

24 TO 55 ENGINE HP



McCORMICK

McCORMICK X1: A FULL UTILITY OFFERING



Perfect for homeowners, hobby farmers, and anyone needing a dependable compact tractor to do work around the homestead. All eleven models, from 24 to 55 engine horsepower, are designed from the ground up to dish out power and performance in a wide variety of applications. With rugged steel and cast iron construction, 4-wheel drive, a choice of transmissions, and robust hydraulic system, the X1 lineup delivers everything you have come to expect from a McCormick tractor. Whether used for loader work, grading, tilling, snow removal, or landscaping, there is an X1 model that will go above and beyond to get the job done.

THE X1.37

The X1.37 is a 37HP cab model with choice of mechanical (X1.37C) or hydrostatic transmission (X1.37HC). Like the current X1 series, the X1.37 model is a heavily built and reliable machine with comfortable and simple operation.



KEY FEATURES:

Engine

- 4-cylinder, 2.0L built by Kukje
- 37 rated HP, 33 PTO HP
- Tier 4 final emissions using only DOC and DPF

Transmission

- Available 12x12 Mechanical or 3 Range Hydrostatic

Cab

- Designed for increased visibility and operator space
- High level of features come standard
- Factory cab – quiet and well insulated

PTO

- Independent PTO system
- Choice of 540 and 540E
- "Auto" and "Link" modes of operation

Frame

- Heavy built, over 4,195 lbs
- Cast iron front axle, rear end, and transmission housing
- 71 inch wheelbase for stability
- Steel single piece hood
- Steel Fenders

Front Axle

- Cast iron build
- One of the heaviest in the industry
- 56 degree steering angle with 10 degrees of camber for increased maneuverability
- Hydraulic power steering

Loader

- L160C loader designed by ALO

Hydraulics

- 11.1 gpm (42 lpm) main pump
- 5 gpm (19 lpm) steering pump

3 Point Hitch

- 3,306 lbs (1500kg) lift capacity at ball ends
- Standard category 1 telescoping link ends

McCORMICK X1: THE ULTIMATE IN UTILITY

Loader Model	C12	C16	C18	
Tool Carrier	Pin-On	Skid Steer	Skid Steer	
Lift Height at Bucket Pivot Pin	in (mm)	82 (2082)	99 (2514)	109 (2768)
Lift Capacity to Max Height 19.6" Forward of Pivot	lb (kg)	770 (349)	1520 (689)	2050 (929)
Lift Capacity to 59" Lift Height (39" for C12) 19.6" Fwd of Pin	lb (kg)	880 (399)	1910 (866)	2660 (1206)
Breakout Force at Groundline 19.6" Forward of Pivot	lbs (kg)	1120 (508)	2370 (1075)	3240 (1469)
Bucket Rollback Force at Groundline 19.6" Forward of Pivot	lbs (kg)	1420 (644)	3720 (1687)	4440 (2013)
Compatible Tractor Models	X1.25H	X1.35 X1.35H X1.37C X1.37HC	X1.45 X1.45C X1.45HC X1.55H X1.55C X1.55HC	

Belly Mower Model	BM60
Cutting Width	in (mm)
Cutting Height	in (mm)
Height Adjustment	3-point lift controls
Number of Blades	3
Drive System	Belt drive from mid PTO
Compatible Tractor Models	X1.25H



A PLATFORM FOR EVERY OPERATION



MCCORMICK

Tractor Model		X1.25H	X1.35	X1.35H	X1.37C	X1.37HC				
Rated Engine Power	HP (kW)	24 (18)	35 (26)	35 (26)	37 (27.1)	37 (27.1)				
Rated Engine Speed		2600 RPM								
Rated PTO Power	HP (kW)	18 (13)	29 (21)	29 (21)	33 (24.2)	32 (23.5)				
Engine Type		3-cylinder diesel				4-cylinder diesel				
Displacement		1.2 liter (73 in ³)		1.7 Liter (104 in ³)		2.01 Liter (127.1 in ³)				
Aspiration		Natural								
Emissions System		EPA Tier 4	Tier 4, using combined DOC + DPF							
Fuel Capacity	gal (liters)	6.2 (23.6)	9.3 (35), tank under platform			12 (45), ground level tank				
Transmission Type		Hydrostatic	Mechanical	Hydrostatic	Mechanical	Hydrostatic				
Main Clutch		Dry single disc		None	Dry single disc	None				
Speeds		2-range HST	12F x 12R	3-range HST	12F x 12R	3-Range HST				
Shuttle Type		2 Foot pedals	Synchronized	2 Foot pedals	Synchronized	2 Foot pedals				
Differential Lock		Mechanical, heel pedal								
Rear Brakes	Wet disc brakes with R and L pedals		Wet disc brakes with suspended R and L pedals							
Front Axle Type	4wd with mechanical engagement		4wd with mechanical engagement, 62-degree steering angle							
Rear PTO Type	540 RPM, live transmission driven		Independent, electronically engaged, 540 and 540E standard							
Mid PTO	Standard, 2500 RPM		Not available							
Hydraulic System		Open center system								
Hyd. Flow at Remotes	gpm (lpm)	4.8 (18.2)	8.9 (34)		11.1 (42)	10.4 (39.4)				
Loader Joystick		Mounted to loader sub frame		Standard with 2 mid-mount valves						
Rear Remote Valves		1 optional	2 standard							
3-pt Type		Category I	Category I with telescopic stabilizers and lower links							
3-pt Lift Capacity	lb (kg)	1,500 lbs (680) at ball ends	3,306 (1500) at ball ends; 2,425 (1100) at 24"							
Operator's Area		Folding ROPS, right and left entry, rubber foot deck cover				Cab with HVAC, 2 doors, flat foot deck				
Seat and Steering		Vinyl seat, hydrostatic steering	Adjustable vinyl seat, tilt steering wheel, hydrostatic steering							
Wheelbase	in (mm)	60 (1530)	70.9 (1800)			71.1 (1,806)				
Height over ROPS/Cab	in (mm)	88 (2240)	94 (2390)	94 (2390)	96.8 (2,460)					
Base Weight	lb (kg)	1,810 (821)	4,053 (1840)	4,053 (1840)	4,211 (1,910)	4,195 (1,903)				

SPECIFICATIONS

X1.45	X1.45C	X1.45HC	X1.55H	X1.55C	X1.55HC					
47 (35)	47 (35)	47 (35)	55 (41)	55 (41)	55 (41)					
2600 RPM										
42 (31)	42 (31)	42 (31)	47 (35)	47 (35)	47 (35)					
4-cylinder diesel										
2.3 Liter (140 in ³)										
Natural			Turbocharged							
Tier 4, using combined DOC + DPF										
9.3 (35), tank under platform										
Mechanical	Hydrostatic	Hydrostatic	Mechanical	Hydrostatic						
Dry single disc	None	None	Dry single disc	None						
12F x 12R	3-range HST	3-range HST	12F x 12R	3-range HST						
Synchronized	2 Foot pedals	2 Foot pedals	Synchronized	2 Foot pedals						
Mechanical, heel pedal										
Wet disc brakes with suspended R and L pedals										
4wd with mechanical engagement, 62-degree steering angle										
Independent, electronically engaged, 540 and 540E standard										
Not available										
Open center system										
11.1 (42)				11.1 (42)						
Standard with 2 mid-mount valves										
2 standard										
Category I with telescopic stabilizers and lower links										
3,306 (1500) at ball ends; 2,425 (1100) at 24"										
Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck	Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck							
Adjustable vinyl seat, tilt steering wheel, hydrostatic steering										
70.9 (1800)										
96 (2440)	97 (2460)	97 (2460)	96 (2440)	97 (2460)	97 (2460)					
4,118 (1870)	4,442 (2015)	4,442 (2015)	4,118 (1870)	4,442 (2015)	4,453 (2020)					

McCORMICK



McCormick North America
www.McCormickNA.com

updated: 03.10.20

