



# McCORMICK

9000 **IS**

9000 **AR**



# MCCORMICK


9000

9095  
IS  
AR

90105  
IS  
AR

9000		9095 IS AR	90105 IS AR
<b>Engine</b>		(TIER 3)	(TIER 3)
constructor		FPT	FPT
direct injection		mechanical	mechanical
model		F5A	F5A
max. power (ISO rating)	HP/kW	88 / 65	95 / 70
rated speed	rpm	2300	2300
max. torque	Nm	350	390
max. torque speed	rpm	1300	1250
displacement	cm <sup>3</sup>	3200	3200
cylinders / valves		4Turbo / 8	4Turbo / 8
water cooling		STD	STD
fuel tank capacity	litres	60	60
<b>Reverse shuttle</b>			
control			mechanical
wet disc clutch			STD
<b>Transmission</b>			
standard gearbox 16FWD + 16REV			STD
max. speed 40 km/h			STD
<b>Power take-off</b>			
control			electrohydraulic
2 speeds 540/750 rpm			STD
2 speeds 540/1000 rpm			OPT
ground speed PTO			STD
<b>Front axle</b>			
four-wheel drive			electrohydraulic engagement
max. oscillation angle			± 15 degrees
electrohydraulic differential locks			STD
<b>Brakes</b>			
control			hydraulic
rear wet disc brakes			STD
front wet disc brakes			STD
<b>Power lift / Hydraulic system</b>			
rise/lower/float control (STD)			draft and position control (OPT)
electropneumatic suspension for implements			OPT (only IS)
lift capacity			kg 2300
hydraulic pump flow (lift + steering system)			l/min 50 + 31
standard three-point hitch with quick couplings			2 <sup>a</sup> cat
2-way adjust. three-point hitch with quick couplings			OPT
no. 2 rear remote valves (1DE + 1DE Float)			STD
no. 4 rear remote valves (2DE + 2DE Float)			OPT
free return			STD
joystick for proportional control of hydr. system			OPT
<b>Driving position</b>			
platform suspended on silent-blocks			STD
automatic reverse drive system			STD
sprung seat			STD
<b>Cab</b>			
enclosed cab heated			OPT
air conditioning			OPT
<b>Weights (in running order without driver)</b>			
total	kg	2360(IS) - 2200(AR)	
<b>Dimensions</b>			
overhang	mm	1260	
wheelbase	mm	1495	
overall length	mm	3735	
ground clearance	min/max mm	310 / 295	
height to steering wheel	mm	1265	
height to ROPS min/max	min/max mm	2455 / 2425	
track front / rear	min/max mm	1106/1490(IS) - 892/1198(AR)	
width front / rear	min/max mm	1393/1750(IS) - 1179/1513(AR)	

Key: STD = standard; OPT = option; - = not available

Cod. MCM277/0214  I.P.

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.