



GALLIGNANI

SQUARE BALERS



3690 | 5690 GOLD

SPECIFICATION

5690

3690

RECOMMENDED TRACTOR ENGINE POWER	50hp	40hp
PERFORMANCE (Approximate for 1m long bales, in ideal work conditions)		
Bale weight - Straw	20-25 kg	15-20 kg
Bale weight - Hay	25-35 kg	20-30 kg
Productivity	500 Bales / Hour	400 Bales / Hour
PICK-UP		
Picking width including flap	180 cm	170 cm
Net pick-up width (wall-to-wall)	158 cm	156 cm
Picking system	5 Bars with 21 Teeth	4 Bars with 21 Teeth
Hydraulic adjustment of pick-up height	Optional	Optional
Sensing wheel (RH side)	Standard	Optional
COMPRESSION CHAMBER AND BALE SIZE		
Bale section	36x46 cm	36x46 cm
Ram travel and strokes/min (at 610 PTO rpm)	73 cm / 104 spm	66 cm / 100 spm
KNOTTER		
Knotter types	2 Twines, 3 Twines or 2 Wires	2 Twines or 2 Wires
Centralized knotter lubrication system	Optional, Oil Type	Optional, Oil Type
Double knotter fan	Standard	Optional
DRAWBAR		
Mechanical adjustment	STD	STD
Hydraulic adjustment	Optional	Optional
DRIVELINES		
Knotter and first fork	Chain	Chain
Pick-up	Belt	Belt
Cardan shaft	Included	Included
Wide angle cardan shaft	Standard	Optional
TWINE BOX		
	8 reels	4 reels
ACCESSORIES		
Road lights	Optional	Optional
Mechanical bale counter	Standard	Standard
DIMENSIONS & WEIGHTS		
Width	250 cm	240 cm
Length	511 cm	414 cm
Height	182 cm	172 cm
Wheel size LH	10.0/75-15	10.0/80-12
Wheel size RH	10.0/80-12	7.00-12
Weight	1.800 kg	1.380 kg

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

STD: Standard OPT: Optional - : Not Available



SPRING LOADED PICK-UP WITH FLARED INTAKE



GALLIGNANI KNOTTER



BALE SLIDE

MAART/2019