



GALLIGNANI

WRAPPER



G660

SPECIFICATION G660

TYPE

Turntable 3-Point Mounted	-
Turntable - Trailed	STD
Satellite - Trailed	-
Bale Loading	Side Arm

DIMENSIONS & WEIGHTS

Lenght	cm	432
Width (on Road)	cm	252
Height	cm	230
Weight	kg	950

BALE SIZE

Diameter (Max)	cm	120-160
Width (Max)	cm	130
Weight (Max)	kg	1000

TYPE OF CONTROL

Teleflex Cable	STD
Electronic Proportional Joystick	-
AutoStop Device	STD
Bale Count / Rev Count	STD
Programmable Computer Plus Joystick	-
Remote Radio-Control (RF Norm Compliant)	-

PLATFORM

Powered Rollers	2
Roller Diameter	cm 24,5
Distance Between Rollers	cm 111
Height at Rollers	cm 89
Platform Belts	4
Bale Centering Rollers	2

FILM PRE-STRETCH UNIT

Dispenser / Film Size	1 x 750
Film Cut-and-Link Device	STD
Film Spool Size (Max)	cm 75/28
Film Pre-Stretch Ratio	% 70
Film Overlap	% 50

OTHER SPECS

Wheels	10.0/80-12
Spare Film Holder	-
Hydraulic Connections	1 DA or 1 SA with free flow return
Min. Pump Flow	l/min 26

OPTIONS

Bale on-end Turner	OPT
Extra Spare Film Holder	2-3
Road Lights	OPT

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

STD: Standard OPT: Optional - : Not Available



Pivoting wheel, a very practical solution for stability and limited width. The RH wheel has two positions: fully out for great stability at work and loading, fully inside to reduce width during on road circulation.



The operator can control all wrapping functions by means of **teleflex cables – version M** – or by means of the **proportional joystick** (for accurate and efficient function control) – **version J**. Both the cable and the joystick control units can be placed on board the machine or directly on the tractor for operation in full comfort and safety.



Film pre-stretch unit: the aluminium rollers ensure a smooth and constant film stretch. The groves on the surface of the rollers allow residual water and air to disperse while film is being stretched. The replacement of the film roll is made easy and simple.



The operator can control all wrapping functions by means of Teleflex cables.



Film holder and Pre-Stretch unit.



Automatic film cut and hold system.



4x Platform Belts & 2x Centering Rollers