

# X4+



X4.060 - X4.070 - X4.080



**MCCORMICK**

Power Technology.

		X4.060	X4.070	X4.080
ENGINE PERFORMANCE				
Rated power (97/68 CE - ISO TR 14396)	hp/kW	61 / 45	68 / 50	75 / 55
Max power (97/68 CE - ISO TR 14396)	hp/kW	61 / 45	68 / 50	75 / 55
Rated engine speed	rpm	2200		
Engine speed at max power	rpm	1400		
Max torque at 1400 rpm - Stage V (Tier 4 Final)	Nm	285 (279)	310 (299)	310 (299)
Manufacturer		KOHLER		
Exhaust after-treatment - Stage V (Tier 4 Final)		DOC-DPF (DOC)		
Cylinders / Displacement / Valves		4 / 2.5L / 16		
Engine Memo Switch		●		
CAPACITIES				
Fuel tank	l	85		
CLUTCH				
Type		● mechanical		
TRANSMISSION				
No. of gears - std		● 24FWD + 24REV with synchro shuttle		
No. of gears - option 1		○ 12FWD + 12REV with RPS		
Minimum speed without creeper	km/h	0.43 with 24+24 Hi-Lo - 0.50 with RPS (IR 650mm)		
REAR PTO				
Type		● mechanical		
Speeds	rpm	● 540/540E		
Ground speed PTO		●		
FRONT AND REAR AXLES				
Front rigid axle		●		
Traction type		4WD		
Front differential lock		● limited slip - ○ w/o differential lock		
Rear differential lock		● mechanical		
BRAKING SYSTEM				
Front braking system		● automatic 4WD engagement when braking		
Rear braking system		ramp brakes		
Trailer braking system		○ 2-line hydraulic brake as per MR - ○ single-line hydraulic brake or CUNA ○ 2-line pneumatic brake*		
HYDRAULIC SYSTEM				
Hydraulic pump for rear hitch & remote valves + steering - flow rate		● 52 + 30 l/min		
Rear remote valves - type, number		mechanical, 2 - 3		
Free-flow return		●		
REAR 3-POINT HITCH				
Rear hitch control		● mechanical		
Category - coupler type		II - ○ fixed ball ends   ○ quick-hitch hooks   ○ telescopic lower links		
Ergonomic Lift System (E.L.S.)		○		
Max lifting capacity at hitch points	kg	● 3000		
FRONT 3-POINT HITCH				
Front hitch		*		
FRONT PTO				
Type - Speed		*		
CAB				
Total View Slim cab mounted on silent blocks		●		
In-cab noise level	dB(A)	82		
Heating / Climate control system		● heat and ventilation - ○ manual climate control		
Platform version		○		
MISCELLANEOUS				
McCormick Fleet Management - ready		●		
WEIGHTS AND DIMENSIONS				
Wheelbase	mm	2110		
Max height over cab without beacon lights	mm	2433 - measured with tires 320/70R20 - 420/70R28		
Standard weight measured with average specs	kg	3200		
Gross vehicle weight	kg	5100		
Max front and rear tire size - (Index Radius - IR)	mm	320/70R24 (IR 525mm) - 480/70R30 (IR 700mm)		

**Key:** ● standard ○ option \* aftermarket

All data and illustrations provided in this brochure are for information purposes only and can be changed.