

X5HC

X5.100HC / X1.110HC




McCORMICK

Power Technology.

SPECIFICATIONS

| Tractor Model | | X5.100 HC | X5.110 HC |
|---|---|----------------|-----------|
| Engine | | | |
| Max. Engine HP (ISO) @ 2200 RPM | HP (kW) | 95.2 / 70 | 102 / 75 |
| Max. PTO HP* (ISO) @ 2200 RPM | HP (kW) | 80 / 59 | 88 / 65 |
| Max. Engine Torque @ 1400 RPM | lb ft (Nm) | 395 | 430 |
| Engine Type | FPT F36 engine Tier 5, TACR, DOC + SCRoF, 3,6L, 4 cyl 16v | | |
| Engine Size | 3.6L, 4-Cylinder | | |
| Fuel Capacity | gal (liter) | 35.6 (135) | |
| Drive Train | | | |
| Standard Transmission | 16 x 16 Transmission with creeper - 30 km/h | | |
| Optional Transmission | Transmission (32 x 32) with hydraulic power shuttle & 2 speed power shift | | |
| Rear Axle | Heavy duty flanged rear axle | | |
| Differential Lock | Front: Hydralock full locking differentials; Rear: Electrohydraulic | | |
| 4wd Front Axle | 4WD Hydralock front axle with integrated brakes | | |
| Tire Type | Radial tires standard | | |
| Hydraulics, 3-point Hitch, PTO | | | |
| Implement Hydraulic System Type | Open center with tandem hydraulic pumps | | |
| Hydraulic Flow Rate | gpm (lpm) | 62 (32) | |
| Rear Remote Valves | 2 Rear spool valves S/D acting | | |
| Rear 3-point Hitch Type | 3-point linkage, Cat. 2, telescopic ball ends, pin-type telescopic stabilizers. Lift capacity 9,920 lb (4,500 kg) | | |
| Max. Rear 3-point Lift Capacity @ Hitch | lb (kg) | 9,920 (4,500) | |
| Rear PTO | 540 / 1000 rpm PTO- Hydraulic engagement, controls on rear fender | | |
| Operator's Area | | | |
| Cab | Cab mounted on silent blocks. True flat deck. Opening front window | | |
| Seat and Front Dash | Cab: Cloth seat, air suspension; tilt and telescopic steering wheel | | |
| Wheelbase | in (mm) | 92.7 (2,355) | |
| Height Over Cab with standard wheel equipment | in (mm) | 112.99 (2,870) | |
| Overall Length with front weights | in (mm) | 9,700 (4,400) | |
| Base Weight without ballast | lb (kg) | 13,227 (6,000) | |

* Manufacturer's calculated estimate