

X6

X6.125 - X6.135



MCCORMICK



McCORMICK X6

MEET YOUR NEW FARMHAND



Each McCormick tractor reflects the passion and dedication of those involved in designing, testing and producing this incredible line-up of tractors. The X6 Series tractors make a statement with power, versatility, and efficiency.

Built to be an economical, reliable “workhorse” around the farm, the X6 Series offers a simple solution to those needing a strong, dependable tractor. This model combines powerful performance with basic features and modern styling.

Boasting a powerful FPT F36 engine, the X6 generates a high sustained torque that keeps the wheels turning and gets work done. Every X6L tractor is designed and built in-house at McCormick factories in Europe.

HIGHLIGHTS

- › Manufactured, Designed, and Engineered by McCormick.
- › 3.6 liter FPT F36 Engine
- › Standard 18-Speed Gearbox
- › Hydraulic Power Shuttle
- › Push-Button 4WD Front Axle
- › 55 degree steering angle
- › Heavy Lifting 3-Point Hitch
- › Large 4-Post Cab with completely flat Foot Deck
- › Digital Front Dash Display
- › 29.05 (110 lpm) Superior Hydraulic System
- › Instructor's Seat
- › 25 mph (40 kph) Transport Speed
- › Fully locking front and rear differentials
- › Closed Center Hydraulic System (2018 models & later)
- › 540 and 1000 dd PTO standard equipment

MODEL	MAX HP	MAX PTO HP
X6.125	119	92
X6.135	127	108





HOOD DESIGN

FAMILY STYLE

CAB

EXCEPTIONAL VISIBILITY

ENGINE

FPT F36 ,3.6L

REAR HITCH

18,480 LB LIFT

FRONT AXLE

4-WHEEL DRIVE

TRANSMISSION

POWER SHUTTLE

REAR PTO

540/1000

FRONT END LOADERS

Loader Model		L51	L56	L58
Loader Type		Non-Self Leveling	Self Leveling	Self Leveling
Max. Lift Height at Pivot Pin	in (mm)	159 (4060)	159 (4060)	159 (4060)
Lift Capacity to Max. Height 31.5" (800 mm) Forward of Pivot Pin	lb (kg)	2,870 (1300)	4,370 (1980)	5,070 (2300)
Breakout Force from Ground Level 31.5" (800 mm) Forward of Pivot Pin	lb (kg)	7,540 (3420)	7,430 (3370)	8,620 (3910)
Lift Capacity to Max Height at Pivot Point	lb (kg)	4,520 (2050)	3,790 (1720)	4,430 (2010)



Tractor Model		X6.125	X6.135
Performance			
Max. ISO Engine HP @ 2200 RPM	HP (kW)	119 (88)	127 (93)
Max. ISO PTO HP @ 2200 RPM*	HP (kW)	92 (67.7)	108 (72.9)
Max. Engine Torque @ 1300 RPM	lb ft	518	
Engine			
Engine Type	FPT F36 engine Stage V, TACR, DOC + SCRoF, 3.6L, 4 -cylinder 16v		
Engine Size	3.6 Liter, 4-cylinder		
Fuel / DEF Capacity	gal (liter)	44.9 (170)	
Drive Train			
Transmission Type	Transmission 36 x 12 with shuttle with Extra Shift (HML)		
Optional Transmission	Transmission 48 x 16 with power shuttle and 3 speed powershift HML		
Rear Axle	Heavy duty rear axle		
Differential Lock	100% Hydralock differential lock		
4wd Front Axle	4WD Hydralock front axle with integrated brakes		
Tire Type	Radial tires standard		
Hydraulics, 3-point Hitch, PTO			
Hydraulic System Type / Max Flow	gpm	Load sensing variable displacement hydraulic pump (110 l/min)	
Hydraulic Flow Rate	gpm	29.05 (110)	
Rear Remote Valves	3 rear hydraulic spool valves (1 Float w. F/D + 1 KO w. F/D + 1STD)		
Rear 3-point Hitch Type	3-point linkage, Category 2 with telescopic ball ends		
Rear 3-point Lift Capacity @ Hitch	lb (kg)	4850.17 (2200)	
Rear PTO	PTO 2 speeds, 540/1000 rpm		
Operator's Area			
Cab	Cab on silent-blocks with fixed front windscreen		
Seat and Front Dash	Cloth seat, air suspension, tilt and telescopic steering wheel		
Wheelbase	in (mm)	95.27 (2,420)	
Height Over Cab <i>with standard wheel equipment</i>	in (mm)	103.26 (2,623)	
Base Weight <i>without ballast</i>	lb (kg)	17,636 (8,000)	

* Manufacturers calculated estimate. +/- 5% tolerance.

**Open Center System on all models 2017 and earlier



McCormick North America
www.McCormickNA.com

updated: August 2023

